



SPECIFICATIONS

- FLUID : COMPRESSED AIR
- MAX. WORKING PRESSURE : 1.0MPa
- PROOF PRESSURE : 1.5MPa
- AMBIENT TEMPERATURE : -5~60° c
- WORKING SPEED : 50~500mm/s
(CUSHION STROKE IS EXCEPTED)
- CUSHION : ATTACHED
- COATING COLOR : STANDARD OF KONAN
- GRADE OF SCREW : JIS 6H.6g
- PISTON ROD & INTERNAL SURFACE OF CYLINDER TUBE : HARD CHROMIUM PLATED
- INTERNAL OF CYLINDER PARTS IS TREATMENT RUSTLESS
- CONSTRUCTIONS & DETAILS : SEE CATALOG

MODEL: CP66-220X1650-G61710

△X						認可 APR.	検図 CHK.	担当 DES.	尺度 SCL.	名称 NAME	甲南電機株式会社 KONAN ELECTRIC CO.,LTD.	第三角法
△X									N:O	TYPE TC		
△X										φ220X1650ST	500-61710	REV.
訂番 REV.	書類番号 DOC.NO.	内容 CONTENTS	認可 APR.	検図 CHK.	担当 DES.	'26.04.07	'26.04.07	'26.04.07	SIZE=A4	AIR CYLINDER	(S-IN-80-002)	△ 0